

Elite Plus technical data

Click System	UNILIN
Size	180 x 1220 mm
Total thickness	6 mm
EVA backing foam	DRY BACK
Wear layer	0,55 mm
Kg / sqm	6,8 kg
Kg / box	22,40 kg
Tiles / box	15
Sqm / box	3,294 m ²
Bevel	SOFT
Classification EN429	33 / 42
Wear group EN649:2011	T
Colour fastness to light EN ISO105 B02:2013	4 - 5
Dimensional stability ISO23999:2012	0,05 %
Expansion in temperature change from 23° C - 45° C	0,020 %
Shrinkage in temperature change from 23° C - 5° C	-0,095 %
Curling after heat exposure ISO23999:2012	0,5 mm
Fire behavior EN13501:2007 + A1:2009	Bfl-S1
Slip resistant UNE-ENV 12633:2003	CLASS 2
Formaldehyde emissions EN717-1:2004	PASS
Castor chair test EN425:2002	PASS
Swelling in thickness after immersion in water GB-T17657-2013 CLAUSE 4.5	0,16 %
Determination of residual indentation EN ISO24343-1:2012	0,41 mm
Suitable for water heating	MAX. 32° C
Suitable for electric heating	NO SUITABLE
Warranty domestic use*	20
Warranty comercial use*	8

*Check carefully the Warranty Conditions and Installation Method.

Elite Plus is composed by:

1. High resistance PU protective layer
2. PVC decorative layer
3. Vinyl sheet
4. WPC core

