

## Technical data

Click system	<b>UNILIN</b>	
Size	<b>225 x 1220 mm   400 x 800 mm</b>	
Total thickness	<b>6 mm</b>	
Backing	<b>1,5 mm EVA + PE</b>	
Wear layer	<b>0,55 mm</b>	
Bevel	<b>Microbevel   Painted V-bevel</b>	
Classification EN429	<b>33 / 42</b>	
Wear group EN649:2011	<b>T</b>	
Colour fastness to light EN ISO105 B02:2014	<b>6</b>	
Dimensional stability ISO23999:2018	Manufacturing direction	<b>0,05 %</b>
	Across-manufacturing direction	<b>0,015 %</b>
Curling after heat exposure ISO23999:2018	<b>0 mm</b>	
Fire behavior EN 13501-1-2018 Clause 9, EN ISO 9239-1:2010, EN ISO 11925-2:2010, COR1-2011	<b>Bfl-s1</b>	
Slip resistance DIN 51130:2014-02	<b>R10</b>	
Castor chair test EN ISO 4918:2016	<b>PASS</b>	
Determination of residual indentation EN ISO 24343-1:2007 (R2015)	<b>&lt; 0,21 mm</b>	
Staining and resistance to chemicals EN 26987:2012	<b>PASS</b>	
Dynamic coefficient of friction on dry floor surface EN 13893:2002	<b>DS (≥ 0,30°)</b>	
Movement of furniture leg resistance EN 424:2001	<b>PASS</b>	
VOC emission testing EN ISO 16000-9:2006 / COR-1-2007, ISO 16000-6:2001	<b>A+</b>	
Thermal conductivity and thermal resistance EN 12664:2001	<b>0,106 W/(m.K)   0,057(m².K)/W</b>	
Improvement of impact sound ISO 10140-1:2016	<b>19 dB</b>	
Sound insulation ISO 717-2:2013	<b>19 dB</b>	
Warranty domestic use*	<b>20</b>	
Warranty comercial use*	<b>10</b>	